

GF6019D1

500A 1000V Dc Power Source With Dc Energy Meter Calibrator

GF6019D1 high precision DC power source is a standard voltage and current source newly designed and developed by GFUVE. In order to meet the current requirement for verification of DC energy meter in the market, it follows the international standards of DC energy meters, adopts the latest technology, and the main elements of the devices are all industrial-grade, which can support large current signals from 0 to 600 A DC, and the accuracy level is better than 0.05%; 0~1150V DC voltage output, the accuracy level is better than 0.05%; 0~5V DC voltage analog shunt output, the accuracy level is 0.05%, and supports the voltage and current output ripple superposition function, which can be used for the virtual load verification of the DC energy meter, the ripple interference test, or as a separate standard DC voltage source, standard DC current source, and standard DC power source. It can test DC energy meter basic error, starting test, creep test, error of time of day.

The GF6019D1 DC energy meter calibrator adopts a 19-inch color TFT touch LCD screen, with a clear and simple interface, convenient operation and good visual effect. The core module adopts 32-bit high-speed DSP combined with adaptive Lagrangian interpolation algorithm to eliminate the hardware asynchronous error of DC ripple, and the waveform quantization adopts 32-bit dual modulation output technology to ensure high output accuracy. The device output has overload, short circuit and overheating protection, which is safe and reliable.

Features

1. Support program by user;
2. Testing EV DC charging pile;
3. DC power source integrated;
4. Test by automatic or manual;
5. Wide range 0-600A/0-1150V;
6. Start testing and creep testing;
7. User friendly menu guided operation;
8. Built-in DC meter verification scheme;
9. Recorder 10000 sets energy meter data;
10. Multi-range, high precision 0.02%/0.05%;
11. DC current source and DC voltage source;
12. Easy verification and analysis of DC meter;
13. Adopting DSP+MCU processor technology;
14. Using software calibration, stable and reliable;
15. Overload, short circuit, open circuit protection;
16. Testing all kinds of DC ammeter & DC voltmeter;
17. Automatic operation without need of an external PC;
18. Testing all kinds of DC energy meter & DC power meter;
19. 19 inch TFT touch screen, English display, easy to operate;
20. Especially configured USB stick for storage of customer data;



Application

1. Universities;
2. DC energy meter R & D;
3. Electrical testing center;
4. Transducer manufacturers;
5. Digital meter manufacturers;
6. Pointer meter manufacturers;
7. Railway electrical department;
8. ISO17025 Electrical laboratory;
9. DC panel meter manufacturers;
10. DC power meter manufacturers;
11. National metrology and testing department;
12. Electricity power bureau & power company;
13. Electrical Department of industrial and mining enterprises;

Parameters

Electrical parameters	
Accuracy class	0.05%, 0.02%
Power supply	Single phase AC 220V±10% or 110 V±10%, 50/60 Hz
DC Voltage output	
Range	65V, 500V, 1000V; Small Signal: 4 mV≤Uo≤5 V
Adjustment range	(0-120)% RG
Adjustment resolution	0.01% RG, 0.1% RG, 1% RG, 10% RG
Accuracy	0.05% or 0.02%
Stability	0.01% RG / 1 min
Distortion degree	Better than 0.1% (not capacitive load)
Load Capacity	Max 50VA
Ripple	Frequency: 20~500Hz
Ripple contents	≤0.5%
Full load regulation rate	Less than 0.01% RG
Full load regulation time	Less than 10ms
Temperature drift	8 PPM/°C
Long-term stability	60 PPM/year
DC Current output	
Range	0.001A, 0.005A, 0.02A, 0.05A, 0.2A, 1A, 3A, 10A, 20A, 30A, 60A, 600A;
Adjustment range	(0-120)% RG
Adjustment resolution	0.01% RG, 0.1% RG, 1% RG, 10% RG
Accuracy	0.05% or 0.02%
Stability	0.01% RG/1 min
Distortion degree	Better than 0.1% (not capacitive load)
Load Capacity	max 1200VA

Electrical parameters - continued

DC Current output - continued

Ripple	Frequency: 20~600Hz
Ripple contents	≤1%
Full load regulation rate	Less than 0.01% RG
Full load regulation time	Less than 10mS
Temperature drift	8 PPM/°C
Long-term stability	60 PPM/year

DC Power output

Accuracy	0.05%, 0.02%
Stability	0.01% RG / 1 min

Functions

Communication Port	RS232, USB, 10/100M LAN
Programmable controlled	Yes
LCD	15 inch touch TFT color display
Energy accumulation	Optional
Energy pulse(input & output)	Optional
Keyboard	Optional
PC control software	Optional

Standard

Standard	JJF1284-2011; JJF1597-2016; JJF1638-2017; JJG064-2021; JJG6-2011; JJF77-2015; JJG69-2017; JJG193-2109; IEC 62052-11:2020; IEC 62053-41: 2021;
----------	---

Safety

Isolation protection	IEC 61010-1:2001
Measurement Category	300 V CAT III, 600 V CAT II
Degree of protection	IP20
Declaration of conformity	CE & CNAS certified

Mechanical parameters

Dimensions (W×D×H) (mm)	750x780x1250
Weight (kg)	150

Environmental conditions

Operating temperature	-50°C to 50°C
Storage conditions	-30°C to 75°C
Relative humidity	≤85%